

PRODUCT SPECIFICATION

GP Portable PowerBank Model : M20B

Revision History


Revision	Date	Initiator	Reason for Change
0.0	25 Aug 2021	Kevin Chan	Draft Release
0.1	1 Nov 2021	Kevin Chan	Updated weight and IEC
0.2	11 Nov 2021	Kevin Chan	Updated input specs, recharge time and remarks on reverse charging
0.3	20 Jan 2022	Kevin Chan	Updated input rating to 5V/3.0A

Prepared By	Approved By
Kevin Chan	Kevin Chan
Date: 25 Aug 2021	Date: 25 Aug 2021

GP Batteries

Model no.: M20B

Product Specification



Product Name : GP Portable PowerBank M20B

Description : M-series v2 20000mAh PD 22.5W PowerBank

Battery Rating : Lithium Polymer 3.7V 20000mAh 74Wh

Input : [USB-C PD] DC 5V/3.0A, 9V/2.0A, 12V/1.5A (18.0W Max.)

Output : [USB-C PD] DC 5V/3.0A, 9V/2.22A, 12V/1.67A (20.0W Max.)

[USB-A] DC 5V/4.5A, 9V/2.0A, 12V/1.5A (22.5W Max.)

[USB-C+USB-A] DC 5.0V/3.0A (15W Max.)

Total output : 22.5W Max.

Application : Charge mobile and electronic devices with USB input

Recharging Time : 6.5 hours by 9V/2A via USB-C port

Operation Temperature : 5°C to 35°C



Product Specification

Safety protection : 1) Over voltage protection

2) Over current protection

3) Over charging and discharging protection

Model no.: M20B

4) Short circuit protection

5) Over temperature protection

6) Loop back protection

LED Indication : Charging & Discharging the Portable PowerBank

There are four diffused white LEDs for battery status, ☼: LED blinking, ∘: LED off, •: LED on, with ±5% error) There is one blue LED to indicate fast charging.

Item	Scope	Status				
Charge	Power Level	LED #1	LED #2	LED #3	LED #4	
indication	100%	•	•	•	•	
	75-100%	•	•	•	☆	
	50-75%	•	•	☼	0	
	25-50%	•	☼	0	0	
	0-25%	☆	0	0	0	

Press button to show battery status:

Item	Scope	Status				
Discharge	Power Level	LED #1	LED #2	LED #3	LED #4	
and battery	75-100%	•	•	•	•	
level indication	50-75%	•	•	•	0	
	25-50%	•	•	0	0	
	10-25%	•	0	0	0	
	0-10%	☼	0	0	0	

Dimensions : 138 (L) x 67 (W) x 27 (H) mm +/-0.5mm

Weight : 370g +/- 10g (TBC)

Certification : CE, FCC, UKCA, RoHS, UN38.3, IEC62133, IEC62368

Bundled cable : 30cm Essential USB-A to USB-C charging cable

Warranty Period : 12 months from ex-factory date

: PowerBank will shut down automatically when it's depleted. Reverse Remarks

charging will happen if the powerbank is completely empty when connected to a device.

Member
Gold Peak Group
Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.