

SKANBATT

Datasheet BAS12-150R

Electrical Specifications

Nominal Voltage	12,8V
Nominal Capacity	150Ah
Nominal Energy	1920Wh
Internal Resistance	≤20mOhm
Self Discharge Rate	<3,5% pr month
Max. Modules in Parallel/Series	4 / 4
Life Cycles	>4000 @0,3C 80% DoD
Chemistry	LiFePO4

Mechanical Specifications

Dimensions (L x W x H)	355mm*180mm*190mm
Weight	15 ±0,2kg
Terminal	M8
Case Material	ABS
Enclosure Protection Rate	IP65

Charge Specifications

Rec. Charge Current	<30A
Max. Charge Current	75A
Rec. Charge Voltage	14,0-14,6V
Rec. Float Voltage	13,6-13,8V
High Voltage Disconnect	14,8V +/-0,1V

Protection Features

Short Circuit Protection	Yes
Low Voltage protection	Yes
High Voltage protection	Yes
Low Temperature protection	Yes
High Temperature protection	Yes
Cell imbalance protection	Yes
Over current protection	Yes

Discharge Specifications

Rec. Discharge Current	<75A
Max. Continuous Discharge Current	150A
Peak Discharge Current	300A <3s@25°C
Short Circuit Protection	2400A @350µs
End of Discharge	10~11V

Temperature Specifications

Short-term Storage Temperature	-40°C to 60°C
Long-term Storage Temperature	-10°C to 45°C
Rec. Storage Temperature	5°C - 15°C @45%-75% SoC
Charge Temperature	0°C - 45°C
Discharge Temperature	-20°C - 60°C

Communications

Bluetooth	No
-----------	----

Others

Mounting orientation	Dynamic: Upright Static: Upright or side
Certifications	CE / UN38.3 / IEC62619 / RoHS