

LOKITHOR

THE ONE

JTC4250



6V&12V | **4250A** | **12V**
 Battery Charger 6A | 10L Gas / 8L Diesel | Battery Tester



SUV



Supercar



Pick-up



Car / MPV



Motorboat



Truck



Motorcycle



UTV / ATV

SPECIFICATIONS



JUMP STARTER

Capacity: 7000mAh 89.6Wh | LiFePO4
 Nominal Voltage: 12.8V
 Starting Voltage: 12V
 Starting Current: 3000A
 Peak Current: 4250A
 Charging Temperature: 0°C to 45°C(32°F to 113°F)
 Storage Temperature: -20°C to 50°C(-4°F to 122°F)
 Operation Temperature: -20°C to 60°C(-4°F to 140°F)
 Service life: >2000 cycles (in good condition)



BATTERY CHARGER

Input AC: 100-240V~50/60HZ 2A Max
 Charging Output: 6V(6A), 12V~15V(6A)Max 90W
 Battery Chemistries: Lead-Acid and LiFePO4
 Battery Types: 6V,12V
 Vehicle Battery Capacity: Up to 120Ah
 Operating Temperature: -10°C to 45°C(14°F to 113°F)
 Low-Voltage Detection: 2V
 IP Rating: IP 65 (w/ Ports closed)



12V BATTERY TESTER

Cranking Test: Supported
 Charging Test: Supported
 Battery Test: Supported
 Bluetooth Connection: Supported
 APP Viewing: Supported



OTHER

USB-A Output: 5V = 3A, 9V = 2A, 12V = 1.5A
 USB-C Input & Output: 5-20V = 3A (PD 60W)
 BX80 Output (Under power supply mode):
 5-20V 0-6A, 90W Max (AC Power)
 5-20V 0-5A, 60W Max (Battery Power)
 LED Lumen: 300 lumens
 Product Dimensions (LxWxH): 264*146.2*109.5mm
 Unit Weight: 2.3kg
 Unit Weight w/Clamps & Accessories: 3.3kg

FEATURES



MULTI-FUNCTIONAL INTEGRATION

Lokithor JTC4250 combines a jump starter, battery tester, and battery charger in one innovative device, offering unparalleled convenience and efficiency for all your automotive needs.



CONNECTMAX TECHNOLOGY

Our state-of-the-art system automatically detects the impedance of the clamp connection to your car battery, ensuring optimal contact every time and maximizing the starting efficiency of your jump starter.



LIFEPO4 SAFE PERFORMANCE

Lokithor's Lithium Iron Phosphate (LiFePO4) battery technology offers safe and stable chemical performance with a long cycle life.



MULTIPLE PROTECTIONS

Overvoltage & Undervoltage & Overcurrent
 High temperature & Low temperature
 Short circuit & Reverse connection

CE FC UN38.3 RoHS UK CA IP65


WHAT'S IN THE BOX




Physical Product



User Manual



USB -A To USB -C Wire



BX80 Clamp (28.5cm)



Power Cable (1.5m)
 *The plug type varies by country or region.

CONTACT US

Grepow Inc.
 290 Lindbergh Ave
 Livermore, CA 94551
 United State

✉ service@lokithor.net

Genspow GmbH
 Ottostr.11
 41352 Korschenbroich
 Germany

🌐 WWW.LOKITHOR.NET



LEARN MORE PRODUCTS



SCAN & DOWNLOAD
 "BAT TEST" APP