



Handling and Storage

- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Cyclic Charge Voltage	14.4 - 14.8V @ 25°C
Float Charge Voltage	13.5 - 13.8V @ 25°C
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

ODS-AGM470FTT

- 3/8 inch threaded front stud terminal
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	1800A
Cold Cranking Amps (CCA)	1300A
HCA	1600A
MCA	1450A
20Hr Nominal Capacity (Ah)	214Ah
10Hr Nominal Capacity (Ah)	190Ah
Reserve Capacity Minutes	475 mins
Terminal	3/8-16" Stud
Torque Spec in-lbs (Nm max)	80 (9.0)
Internal Resistance (mΩ)	3.3 mΩ
Short Circuit (A)	3800A
Recommended Min. Charging Current (A)	19A
UPC	635241140859

Dimensions and Weight

Length	22.9 in / 582 mm
Width	4.9 in / 124 mm
Height (terminals included)	12.5 in / 318 mm
Height (container)	12.5 in / 318 mm
Weight	132 lbs / 59.9 kg

See Line Drawing on next page

Temperature

Operating temperature range -40°F / -40°C to 113°F / +45°C
 Optimum storage temperature 68°F / +20°C

Technical Data Sheet correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters
 2366 Bernville Road
 Reading, PA 19605, USA
 Tel: +1-800-964-2837

EnerSys EMEA
 EH Europe GmbH
 Baarerstrasse 18
 6300 Zug, Switzerland

EnerSys Asia
 No. 85, Tuas Avenue 1
 Singapore 639518
 Tel: +65 6558 7333


Want more info?
Scan code to access
the ODYSSEY® Battery
Literature Library



Line Drawing

ODS-AGM470FTT

ODS-AGM470FTT



ODYSSEY batteries – AGM² Thin Plate Pure Lead (TPPL) Technology

ODYSSEY[®] AGM² Thin Plate Pure Lead (TPPL) batteries feature 99% pure lead plates that are extremely thin, so more of them fit into the battery. More plates mean more power – ODYSSEY AGM² TPPL batteries deliver twice the power and three times the service life of any other conventional battery, outperforming standard AGM or SLI (flooded) batteries in terms of power density, fast-charge acceptance, shelf life, durability and most important – value for your money.

Technical Data Sheet correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters
2366 Bernville Road
Reading, PA 19605, USA
Tel: +1-800-964-2837

EnerSys EMEA
EH Europe GmbH
Baarerstrasse 18
6300 Zug, Switzerland

EnerSys Asia
No. 85, Tuas Avenue 1
Singapore 639518
Tel: +65 6558 7333

Want more info?
Scan code to access
the ODYSSEY[®] Battery
Literature Library

