

SKANBATT

Datasheet PRE24-50BH

Electrical Specifications

Nominal Voltage	25.6V
Nominal Capacity	50Ah
Nominal Energy	1280Wh
Internal Resistance	≤50mOhm
Self Discharge Rate	<3% pr month
Max. Modules in Parallel/Series	16/2
Life Cycles	>6000 @0,3C 80% DoD
Chemistry	LiFePO4

Mechanical Specifications

Dimensions (L x W x H)	307mm*172mm*215mm
Weight	12 ±0,5kg
Terminal	M8 bolts (10-11 Nm)
Case Material	ABS
Enclosure Protection Rate	IP65

Charge Specifications

Rec. Charge Current	<25A
Max. Charge Current	50A
Rec. Charge Voltage	28,4-29,2V
Rec. Float Voltage	27,2-27,6V
High Voltage Disconnect	29,6V +/-0.1V

Protection Features

Short Circuit Protection	Yes
Low Voltage protection	Yes
High Voltage protection	Yes
Low Temperature protection	Yes
High Temperature protection	Yes
Cell imbalance protection	Yes
Over current protection	Yes

Discharge Specifications

Rec. Discharge Current	<25A
Max. Continuous Discharge Current	50A
Peak Discharge Current	160A <3@25°C
Short Circuit Protection	640A@300µs
End of Discharge	20~22V

Temperature Specifications

Short-term Storage Temperature	-40°C to 60°C
Long-term Storage Temperature	-10°C to 45°C
Rec. Storage Temperature	5°C - 15°C @45%-75% SoC
Charge Temperature	-20°C - 55°C
Discharge Temperature	-20°C - 60°C

Communications

Bluetooth	Yes
OTA	Yes

Others

Mounting orientation	Dynamic: Upright Static: Upright or side
Certifications	UN38.3 / CE / IEC62619 / UL1973