
LIFEPO4 LITHIUM BATTERY

S48-314LFP STACK-LV HE







Series	S-SERIES LFP ESS	Warranty	See Warranty Terms
Volts	48	Design	Stackable
Terminal Type		4x M8 Terminals (2+/2-)	
Size & Thread		M8	
Cables		Busbar included	

Charge | Discharge	
Charge Voltage Range	55.2V - 57.6V
Recommended End of Discharge Voltage	48.0 V
End of Discharge Protection Voltage	44.8 V
Recommended Charge Voltage	56.0 V
Recommended Charge Current	

0~10°C (32-50°F)	0.2C	62.8A
10~35°C (50~95°F)	0.5C	150A
35~50°C (95~122°F)	0.2C	62.8A

Charge Mode:
Closed Loop: Follow inverter setup.
Open Loop: Charge at recommended voltage & current by temperature following directions in the S48-314LFP STACK-LV HE Battery Operating Manual.

Max Continuous Charge Current	150 A
Max Continuous Discharge Current	150 A
Charge Temperature Range	-20°C~55°C (-4~131°F)
Discharge Temperature Range	-20°~60°C (-4~140°F)
Storage Temperature Range	Recommended: -5°~45°C (23~113°F) Limit: -25°C~55°C(-13~131°F)

Capacity	
Nominal Capacity	314 AH
Total Energy	16.08 kWh
Nominal Voltage	51.2 V

Safety & Certification

- Prismatic LiFePO4 cells [314Ah prismatic cell] (UL 1642)
- IEC62619 (cell), UN38.3 (cell/pack)
- ROHS (cell), IP52 Rating

Design

- Modular, stackable design
- Up to 15 parallel connectivity*
- Integrated display
- Battery status indication
- CAN bus & RS-485 connectivity
- External breaker access
- PC & Mobile App Connectivity – Setup entirely via the mobile app
- Heating for low temperature operation [-20°C (-4°F) to 0°C(32°F) charging]
- Modular **LFP Stack Base+Top Assembly** (shown)
    - Install up to 3 x S48-314LFP STACK-LV HE units per stack – recommended due to height & weight
    - Install up to 15 units per system in stacks of equal quantities
    - Cannot mix with other capacities of STACK-LV product

Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Current Protection, Low-Temperature Protection, Over-Temperature Protection
- Secondary protection – Internal BMS Switch & Relay, External Breaker Access

Cannot mix with other capacities of STACK-LV models

*UK & European model


48V LFP Profile

Specifications			
Weight	148.7 kg	327.9 lbs	
Length	450 mm	17.7"	
Width	600 mm	23.6"	
Height	410 mm	16.1"	

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	Steel
Handles	Built-in
Internal BMS Model	48200-5G-UL
Expected Cycle Life	>6000 @ 80% DOD (.5C @ 25°C, 80% EOL), >3500 @ 100% DOD (1C @ 25°C, 70% EOL)
Series Connection	No
Parallel Connection	15
Connectivity	1x Link In (internal), 1x Link Out (internal) 1x CAN bus (external) , 1x RS-485 (external) Refer to **S48-314LFP STACK-LV HE Battery Installation Guide** for compatible inverters, communication types & protocols.

Detailed Illustration



ISO9001 ISO14001 OHSAS18001

Rev.#3 | July 2026