INVERTER GENERATOR

LIGHT WEIGHT SERIES

Performance characteristics

- Maintenance-free within 100 hours.
- Ultra quiet, low noise level.
- Size smaller and light weight ,loading Q'ty more than standard.
- Cost effective.
- Parallel Operation Function(Optional)





SC1400i SC2000i(D) SC3500i(D) SC4500i(D) SC6000i(D)

(D)Means dual fuel optional

Model	SC1400i	SC2000i(D)	SC3500i(D)	SC4500i(D)	SC6000i(D)
Frequency	50Hz / 60Hz				
Rated power	1.2kW	1.6kW	3.0kW	4.0kW	5.5kW
Max. power	1.3 kW	2.0kW	3.5kW	4.5kW	6.0kW
AC voltage	120V/240V				
Phase	Single				
Fuel capacity	2.5L	3.0L	6.0L	10.0L	13.5L
Run time(50%-100% load)	4.5 - 2.5h	5 - 3h	5.5 - 3.5h	9.5-4.5h	11- 4.5h
Engine model	SH60C(60cc)	SH80C(80cc)	SH150B(149cc)	SH230B(224cc)	SV320B(322cc)
Start system	Recoil	Recoil	Recoil/E-start	Recoil/E-start	Recoil/E-start
Noise level(@1/4 load, 7m)	59dB	62dB	62dB	62dB	64dB
Parallel ready	Yes				
Dimensions(mm)	430*252*400	505*272*470	500*309*469	541*396*505	610*430*535
Net weight	12kg	15.1kg	24.5kg	39kg	59.2kg
Loading Q'ty(20GP/40HQ)	384/1230	288/720	240/512	126/336	96/264

INVERTER GENERATOR

SUPER QUIET SERIES

Performance characteristics

- Inverter technology for clean power, THD<3%.
- Ultra quiet, low noise level.
- Economy system, electronic speed control function, low fuel consumption.
- Light and portable.
- Parallel Operation Function(Optional)





SC2300i-O(D) SC4000i-O(D)

(D)Means dual fuel optional

Model	SC2300i-O(D)	SC4000i-O(D)
Frequency	50Hz / 60Hz	50Hz / 60Hz
Rated power	1.8kW	3.5kW
Max. power	2.3kW	4.0kW
AC voltage	120V/240V	120V/240V
Phase	Single	Single
Fuel capacity	4.0L	10L
Run time(50%-100% load)	5.5 - 4h	9.0 - 5.5h
Engine model	SC80(80cc)	SV230(223cc)
Start system	Recoil start	Recoil/E-start
Noise level(@1/4 load, 7m)	63dB	58dB
Parallel ready	Yes	Yes
Dimensions(mm)	560*360*530	660*560*650
Net weight	23kg	51kg
Loading Q'ty(20GP/40HQ)	240/496	128/280